



COSHH ASSESSMENT & HAZARD SUMMARY SHEET

Substance / Trade Name:

SIKA 4a Waterstop



Supplier: Everbuild

Toxic Ingredients	*LTEL	*STEL	**COMMENTS
Caustic Potash Glycerol	10mg/m ³	2mg/m ³	TWA

Description of Substance: Light yellow coloured liquid

Hazards: Causes sever skin burns and eye damage, may cause respiratory irritation

PPE



Gloves



Goggles

First Aid

Skin Contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly with difficulty.
Eye Contact	Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In case of contact rinse immediately with plenty of water and seek medical advice. Continue rising eyes on route to hospital. Remove contact lenses. Keep eyes wide open during rinsing.
Inhalation	Move to fresh air.
Ingestion	Clean mouth with water and drink plenty of water. Do not induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Get immediate medical attention.

Storage Conditions: Store in original container. Keep container tightly closed in a dry and well-ventilated place. Keep contained stored upright with the lid closed to avoid leakage.

***LTEL:** Long-term Exposure Limit – 8-hour weighted average (TWA) ref period

***STEL:** Short-term Exposure Limit – 15-min ref period

****WEL:** Workplace Exposure Limit

OES: Occupational Exposure Standard

TID: Total Inhalable Dust

RD: Respirable Dust



Substance / Trade Name: SIKA 4a

Activity / Conditions of Use: Mortar and concrete admixture.

Quantities used: Various

Assessment of risk: Minor risk if used in accordance with guidance.

Recommended control measures: Avoid exceeding the given occupational exposure limits. Do not get in eyes, on skin, or on clothing. For personal protection see above. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.

Spillage Management: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

Disposal: Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

This Risk Assessment applies only to this substance when encountered or used in the activity and / or conditions described above. If there is a change in the activity or conditions in which the substance is encountered or used, a new assessment must be made.

Print name:

Signed:

Date: